MXB376W/MXB476W SPECIFICATIONS

Main Specification	nns
MXB376W/	Base models include: multitasking controller, 50-sheet
MXB476W	RSPF (MXB376W)/100-sheet DSPF (MXB476W), PCL 6 and
	Adobe PostScript® 3™ printing systems, network scanning,
	auto duplexing, 1 x 500-sheet paper drawer, 50-sheet
Tuno	bypass tray. Black developer is included.
Type Display	Desktop monochrome multi-function system 7" (diagonal) colour dot matrix high-resolution touch panel
Dispiay	tilting display. 1,024 x 600 dots (W-SVGA)
Functions	Copy, print, network print, network scan, document filing
	and fax
Copy System	Dry electrostatic transfer/Dual component developer/
	Magnetic brush development/OPC drums/roller fusing/white
Orininala	LED exposure
Originals Max. Original Size	Sheets and bound documents
Output Size	Min. 5.5" x 8.5", Max. 8.5" x 14"
Copy Speed	37/47 ppm
Multiple Copy	Max. 9,999 copies
First Copy Time	MXB376W MXB476W
(in seconds) ²	Platen Glass 5.3 3.7
Warm Up Time	Doc. Feeder 7.3 5.5 30 seconds (from main switch on),
wanii op iniic	20 seconds (from power button on)
Magnification	25% to 400% in 1% increments
	(with document feeder 25%-200%)
Original Feed	50-sheet RSPF (MXB376W), 100-sheet DSPF (MXB476W)
Scan Speed	MXB376W: Up-to 40 ipm
Outstand Ci	MXB476W: Up-to 110 ipm
Original Sizes	5.5" x 8.5", 8.5" x 11", 8.5" x 14", 2" x 3.5" business card
Paper Capacity Paper Feed	Standard: 550 Sheets/Maximum: 2,350 Sheets Standard: (1) 500-sheet paper drawer (letter/statement size)
System	and 50-sheet bypass tray (letter/legal/statement/envelope
Oyotom	size). Optional: up-to 3 additional 600-sheet paper drawers
	(letter/legal/statement).
Paper Weights	Paper drawers: 16 lb. bond to 28 lb. bond. Other paper
and Types	types include plain, pre-printed, recycled, pre-punched,
	letterhead and colour paper.
	Bypass tray: 16-28 lb. bond (plain paper), 13-16 lb. bond
	(thin paper), 28 lb. bond-80 lb. cover (heavy paper), 20-24 lb. bond (Monarch/Com-10 envelope). Also label paper, gloss
	paper, pre-printed, recycled, pre-punched, letterhead, colour
	paper and OHP film.
Duplexing	Standard automatic duplex copying and printing
CPU	Up-to 1.4 GHz multi-processor design
Interface	RJ-45 Ethernet (10/100/1000 Base-T),
	USB 2.0: 2 host ports (front and rear), 1 device port (rear),
Memory	Wireless 802.11 b/g/n Standard 5 GB copy/print (shared)
Hard Disk Drive	500 GB
Copy Resolution	Up-to 600 x 600 dpi
	Modes: Automatic, Text, Text/Photo, Text/Printed-Photo,
-	Printed-Photo, Photo, Map, Pale-Colour Document.
	Settings: Auto or 9 step manual
Halftone	256 gradations/2 levels (monochrome)
Copy Features	Scan-Once Print-Many, electronic sorting, Auto Paper Selection (APS), Auto Magnification Selection (AMS),
	Auto Tray Switching (ATS), black-white reversal, blank
	page skip, card shot, centre erase, centring, cover pages,
	edge erase, image edit, image preview, insert pages, job
	build, job programs, margin shift, mirror image, mixed size
	original, original count, pamphlet style, proof copy, repeat
	layout, stamp, stamp custom image, suppress background,
	toner save mode, transparency inserts, watermark, 2-in-1 /
Account Control	4-in-1 / 8-in-1 multi shot Up-to 1,000 users. Supports user authentication via
Account Control	user-number, local login name/password, LDAP or
	Active Directory® for all modes
Output Tray	Centre Exit Tray (Main): 280 sheets (face down)
Capacity	Inner Finisher: 280 sheets (face down)
Cloud Supported	Google Cloud Print, Google Drive, Gmail,
Services	OneDrive for Business, SharePoint Online, Exchange Online,
Notwork	Box, Dropbox
Network Protocols	TCP/IP (IPv4, IPv6, IPsec), HTTP/HTTPS, IPP/IPP-SSL, FTP/FTPS, SNMPv3, SMTP/SMTP-SSL, POP3/POP3-SSL,
1 10100018	LDAP/LDAP-SSL, 802.1x for Windows and Unix.
	LOTATION OOL, OOL. IN IOI WITHOUTS AND UTIN.

Main Specificati	ons (continued)
Network and	Includes: IP/MAC address filtering, protocol filtering,
Data Security	port control, TLS Encryption, Kerberos, Active Directory
	integration, AES 256 bit data encryption, data overwrite
	(up-to 10 times), End-of-Lease feature
Firmware	Flash ROM with local (USB), network update
Management	capability and firmware update 1 to N with
	SRDM (Sharp Remote Device Manager)
Device Setup	Web-based management/cloning with user/administrator
Service/	Remote Front Panel, remote access to service logs and
Functions	click counts
Accessibility	Free stop tilting front panel, adjustment of key touch sound
Features	and speed, concave key, document feeder free stop, job
	programs, remote front panel, universal grip for paper trays,
	and disable screen timeout
Environmental	International ENERGY STAR Program Ver. 3.0,
Standards	European RoHS, Blue Angel (RAL-UZ205)
Power Power	AC 110-127 VAC, 60 HZ, 15 A receptacle
Consumption	1.44 kW or less
Weight	Approx. 69 lbs. (MXB376W) / 73 lbs. (MXB476W)
Dimensions	Approx. 19-3/8" (w) x 20-3/8" (d) x 25-1/8" (h)
Network Printing	
PDL	Standard PCL compatible 6, Adobe PostScript 3
Resolution	600 x 600 dpi
Print Speed	37/47 ppm (8.5" x 11")
Print Drivers	Windows 7, Windows 8.1, Windows 10, Windows Server® 2008, Windows Server 2008 R2, Windows Server 2012,
	Windows Server 2016, Windows Server 2019, Windows
	PPD, MAC OSX® (including 10.9 to 10.14), all MAC PPD,
	Linux® PPD
Mobile Printing	AirPrint, Android printing framework
	(Sharp Print Service Plugin), Sharpdesk Mobile ³
Print Features	Auto configuration, serverless print release, bar code
	font printing, carbon copy print, chapter inserts, confidential
	print, custom image registration, different cover page/last page/other page, document control, document filing, duplex
	printing, electronic sorting, form overlay, hidden pattern print,
	image rotation, image stamp, image type, job retention,
	layout print, margin shift, network tandem print, N-up
	printing, page interleave, pamphlet style, proof print,
	print and send, stapling, toner save mode, transparency
	inserts, tray status, user authentication, watermarks,
B: .B: .:	zoom print.
Direct Printing	File Types: TIFF, JPEG, PCL, PRN, TXT, PDF, Compact PDF,
	Encrypted PDF, PostScript, DOCX, XLSX, PPTX, and PNG. Methods: FTP, SMB, Web page, Email and USB memory
Resident Fonts	80 outline fonts (PCL), 139 fonts (PS)
Operating	Windows 7, Windows 8.1, Windows 10, Windows Server®
Systems and	2008, Windows Server 2008 R2, Windows Server 2012,
Environments	Windows Server 2016, Windows Server 2019,
	Mac OS X10.9-10.14, UNIX®, Linux®, Citrix®
	(XenApp 5.0-7.15), Windows Remote Desktop Services,
Printing	SAP device types 1 LPR, IPP, IPPS, PAP, Raw TCP (port 9100), FTP, POP3,
Protocols	HTTP, LPD and LPR for Unix
	Timi, El D alla El Historia
Network Scanni	ng System
Scan Modes	Standard: Colour, monochrome, greyscale
Max.	0 5" v 14"
Original Size	8.5" x 14"
Optical Resolution	600 dpi
Output Modes	600 dpi, 400 dpi, 300 dpi, 200 dpi, 150 dpi, 100 dpi
Image	Monochrome Scanning: Uncompressed, G3 (MH),
Compression	G4 (MR/MMR)
	Colour/Greyscale: JPEG (high, middle, low)
	Internet Fax mode: MH/MMR (option) 1
Image Formats	Monochrome: TIFF, PDF, PDF/A, Encrypted PDF, XPS,
	Searchable PDF, DOCX, XLSX, PPTX, TXT, and RTF. Colour/Greyscale: TIFF, JPEG, PDF, PDF/A, Compact PDF,
	Encrypted PDF, XPS, Searchable PDF, DOCX, XLSX, PPTX,
	TXT, and RTF.
	Internet Fax: TIFF-FX, TIFF-F, TIFF-S1

Destinations	Internet fax (option)
One-touch	
Destinations	Up-to 2,000 (combined scan destinations)
Group	
Destinations	Up-to 500
Programs	48 (combined)
Max. Jobs	Up-to 100
Enhanced Email	Standard Gmail connector, standard Exchange connector
Integration	(on-premise and online)
Scanning	HTTP/HTTPS, FTP/FTPS, SMTP/SMTP/SMTP-SSL/ESMTP,
Protocols	POP3, LDAP, S/MIME
Software	Sharpdesk® desktop personal document management
OUTHVAIO	software Sharpdesk Mobile (download)
	dominate charpacer mobile (dominada)
Super G3 Facsin	nile Function
Communication	ino i unouon
Line	Public Switched Telephone Network (PSTN)
Transmission	i dono ovinonoù releptione rictivotiv (i o riv)
Mode	Super G3, G3
Modem Speed	Maximum 33.6 KBPS with auto fallback
Compression	JBIG, MMR, MR, MH
Scanning	JDIG, IVIIVIT, IVIT, IVIT
Method	Sheet fed or manual feed from platen glass
Transmit	400 x 400 dpi (ultra-fine), 200 x 400 dpi (super-fine),
	200 x 200 dpi (fine), 200 x 100 (standard)
Resolution	256 levels
Halftones	
Transmit Speed	Approx. 2 seconds per page in Super G3 mode
Auto Dialing	Up-to 1000 destinations (combined)
Group Dialing	Up-to 500 groups
Inbound Fax	To email address, FTP or SMB using Transmit Terminal
Routing	Identification (TTI), also Document Administration function
	can send blind copy of transmissions and receptions to an
	administrator email address, FTP or SMB location.
Max. Original	11 1 10 5"
Length	Up-to 19.5"
Programs	48 (combined)
Memory	1 GB (shared)
Features	Transaction Reports, Activity Reports, PC Fax, F-Code
	communication, Memory Transmission, Quick On-line
	Transmission, Inbound Fax Routing, Anti-junk Fax Reception,
	Secure Fax Release, Out-of-Paper Memory Reception,
	Auto Redial, Auto Exposure, Chain Dialing, Polling Reception,
	Duplex Reception and ITU-T.37 Internet Fax Option.
Optional Equipm	
MXDS22N	High Stand
MXDS23N	Low Stand
MXCS14N	600-sheet Paper Feed Unit
MXFN32	30-sheet Staple Inner Finisher
MVCCV1	Charle Cartridge for MVFNOO

Network Scanning System (continued)
Scan Email, Desktop, FTP, Folder (SMB), USB, Super G3 fax,

MXFR63U

MXSCX1

MXFWX1L

MXPF10

DVENDFSV

Supplies		
MXB45NT	Toner Cartridge	
MXB45NV	Developer	
MXB45DU	Drum	

Staple Cartridge for MXFN32

Generic Vendor Interface Kit

Internet Fax Kit

Bar Code Font Kit Application Integration Module

Data Security Kit (not available at time of launch)

- ¹ Some features require optional equipment. See your local dealer.
- ² May vary depending on product configuration, machine settings and operating and/or environmental conditions.
- ³ Go to www.sharp.ca for a list of supported devices and operating systems





Qualcomm® DirectOffice®









Design and specifications subject to change without notice. Sharp, Sharp OSA, Sharpdesk, YourSharp, and all related trademarks are trademarks or registered trademarks of Sharp Corporation and/or its affiliated companies. Microsoft, Office 365, Active Directory, Windows, Windows Server, Excel, PowerPoint, OneDrive, and SharePoint are trademarks or registered trademarks of Microsoft Corporation. Android, Chrome, Gmail, Google Drive, Google Cloud Print, and Chromebook are trademarks or registered trademarks of Google LLC. Adobe, the Adobe logo, PostScript, and PostScript 3 are either registered trademarks of trademarks of Adobe in the United States and/or other countries. Qualcomm DirectOffice is a product of Qualcomm Technologies, Inc. and/or its subsidiaries. Qualcomm in Incorporated, registered in the United States and other countries. DirectOffice is a trademark of CSR Imaging US, LP, registered in the United States and other countries, used with permission. All other trademarks are the property of their respective owners. ©2019 Sharp Electronics of Canada Ltd.

