Main Specifications

MXM6570 MXM7570	Base models include: multitasking controller, 150-sheet DSPF, PCL® 6 and Adobe® PostScript® 3™ printing systems, network scanning, auto duplexing, 2,100-sheet tandem paper drawer, 2 x 500-sheet paper drawer, 100-sheet bypass tray.
Type	Monochrome multi-function digital document system
Display	10.1" (diagonally measured) colour dot matrix high-resolution touch panel tilting display. 1024 x 600 dots (W-SVGA)
Functions	Copy, print, network print, network scan, document filing and fax[1]
Copy System	Dry electrostatic transfer/Dual component developer/Magnetic brush development/OPC drums/Belt fusing/white LED exposure
Originals	Sheets and bound documents
Max. Original Size	11" x 17"
Output Size	Min. 5.5" x 8.5", Max. 12" x 18"
Copy Speed	65/75 ppm (8.5" x 11")
Multiple Copy	Max. 9,999 copies

First Copy Time (in seconds)[2]		MXM6570	MXM7570
	Platen Glass	3.9	3.5
	DSPF	5.9	5.4

Warm Up Time	43 seconds (from main power switch on), 27 seconds (from [Power] button on)
Magnification	25% to 400% in 1% increments (with DSPF 25%-200%)
Original Feed	150-sheet DSPF with original size detection
Scan Speed	Up-to 100 ipm simplex, up-to 200 ipm duplex
Original Sizes	5.5" x 8.5", 8.5" x 11", 8.5" x 11" R, 8.5" x 14", 11" x 17"
Paper Capacity	Standard: 3,200 Sheets/Maximum: 6,700 Sheets
Paper Feed System	Standard: Tandem Tray 1 – 1,250 sheets (letter), Tandem Tray 2 – 850 sheets (letter) + (2) 500-sheet paper drawers (letter/legal/ledger/statement) and 100-sheet bypass tray (letter/legal/ledger/statement). Optional: 3,500-sheet large capacity tray (letter) or 3,000-sheet large capacity tray (ledger).
Paper Weights and Types	Tandem drawers: 16 lb. bond to 28 lb. bond. Paper drawers: 16 lb. bond to 80 lb. cover. Other paper types include: plain, recycled, letterhead, pre-printed, pre-punched, and colour paper. Bypass tray: 16-28 lb. bond (plain paper), 15-16 lb. bond (thin paper), 80-110 lb. cover (heavy paper), and tab paper (letter). Also label paper, gloss paper, recycled, letterhead, pre-printed, pre-punched, colour paper and OHP film.
Duplexing	Standard automatic duplex copying and printing
CPU	Up-to 1.4 GHz multi-processor design
Interface	10/100/1000 Base-T Ethernet, USB 2.0: 2 host ports (front and rear), 1 available device port (rear), wireless 802.11 b/g/n
Memory	Standard 5 GB copy/print (shared)
Hard Disk Drive	500 GB
Copy Resolution	Scan: Up-to 600 x 600 dpi Output: Up-to 1200 x 1200 dpi
Copy Modes	Monochrome/Greyscale
Exposure Control	Modes: Automatic, Text, Text/Photo, Text/Printed-Photo, Printed-Photo, Photo, Map, Pale-Colour Document Settings: Auto or 9 step manual
Halftone	256 gradations/2 levels (monochrome)
Copy Features	Scan-Once Print-Many, electronic sorting, offset-stacking, Auto Paper Selection (APS), Auto Magnification Selection (AMS), Auto Tray Switching (ATS), black-white reversal, blank page skip, book copy, book divide, card shot, centre erase, centring, cover pages, dual page copy, edge erase, image edit, image preview, insert pages, job build, job programs, margin shift, mirror image, mixed size original, multi-page enlargement, original count, pamphlet style, proof copy, repeat layout, reserve copy, rotated copy, stamp, stamp custom image, suppress background, tab copy, tab-paper insertion, tandem copy, toner save mode, transparency inserts, watermark, 2-in-1 / 4-in-1 / 8-in-1 multi shot
Account Control	Up-to 1,000 users. Supports user authentication via local, LDAP, and Active Directory® for copy, print, scan and document management.
Output Tray Capacity	Main output tray (top): 250 sheets (face down); optional right side exit tray: 100 sheets (face down)
Cloud Supported Services	Box, Google® Cloud Print, Google Drive, OneDrive® for Business, SharePoint® Online
Network Protocols	TCP/IP (IPv4, IPv6, IPsec), HTTP/HTTPS, IPP/IPP-SSL, FTP/FTPS, SNMPv3, SMTP/SMTP-SSL, POP3/POP3-SSL, LDAP/LDAP-SSL, 802.1x for Windows and Unix.

Main Specifications (continued)

Network and Data Security	Includes: IP/MAC address filtering, protocol filtering, port control, TLS Encryption, Kerberos support, Active Directory integration, data encryption, End-of-Lease, data overwrite (up-to 10x), DoD 5220.22-M
Firmware Management	Flash ROM with local (USB), network update capability and firmware update 1 to N with SRDM (Sharp Remote Device Manager)
Device Setup	Web-based management/cloning with user/administrator level login
Service/ Functions	Remote Front Panel, remote access to service logs and click counts
Accessibility Features	Free stop tilting front panel, adjustment of key touch sound and speed, concave key, document feeder free stop, job programs, remote front panel, universal grip for paper trays and disable screen timeout
Environmental Standards	International Energy Star Program Ver. 2.0, European RoHS
Power Source	110-127 V AC, 60 HZ, 20 A Receptacle
Power Consumption	1.92 kW or less
Weight	Approx. 362 lbs.
Dimensions	Approx. 26" (w) x 30.5" (d) x 48" (h)

Network Printing System

PDL	Standard PCL® 6, Adobe PostScript 3
Resolution	1200 x 1200 dpi
Print Speed	65/75 ppm (8.5" x 11")
Print Drivers	Windows 7, Windows 8.1, Windows 10, Windows Server® 2008, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows PPD, MAC OS X® (including 10.6 to 10.13), all MAC PPD, Linux® PPD
Mobile Printing	AirPrint®, Android™ printing framework (Sharp Print Service Plugin), Sharpdesk® Mobile[3]
Print Features	Auto configuration, serverless print release, bar code font printing, carbon copy print, chapter inserts, confidential print, continuous printing, custom image registration, different cover page/last page/other page, document control, document filing, duplex printing, electronic sorting, folding, form overlay, hidden pattern print, image rotation, image stamp, image type, job bypass print, job retention, layout print, margin shift, multiple pamphlet, network tandem print, N-up printing, offset stacking, page interleave, pamphlet style, poster print, proof print, print and send, punching, stapling, tab paper print, tab printing, toner save mode, transparency inserts, tray status, user authentication, watermarks, zoom print
Direct Printing	File Types: TIFF, JPEG, PCL, PRN, TXT, PDF, Compact PDF, Encrypted PDF, PostScript, DOCX, XLSX, PPTX, and PNG. Methods: FTP, SMB, Web page, Email and USB memory
Resident Fonts	80 outline fonts (PCL), 139 fonts (PS)
Interface	RJ-45 Ethernet 10/100/1000 Base-T, USB 2.0, Wireless
Operating Systems and Environments	Windows® 7, Windows 8.1, Windows 10, Windows Server® 2008, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Mac OS X 10.6-10.13, UNIX®, Linux, Citrix® (XenApp 5.0-7.12), Windows Remote Desktop Services, SAP device types[1]
Printing Protocols	LPR, IPP, IPPS, PAP, Raw TCP (port 9100), FTP, POP3, HTTP, LPD and LPR for Unix

Network Scanning System

Scan Modes	Standard: Colour, monochrome, greyscale
Max. Original Size	11" x 17"
Optical Resolution	600 dpi
Output Modes	600 dpi, 400 dpi, 300 dpi, 200 dpi, 150 dpi, 100 dpi
Image Compression	Monochrome Scanning: Uncompressed, G3 (MH), G4 (MR/MMR) Colour/Greyscale: JPEG (high, middle, low) Internet Fax mode: MH/MMR (option)[1]
Image Formats	Monochrome: TIFF, PDF, PDF/A, Encrypted PDF, XPS, Searchable PDF, DOCX, XLSX, PPTX, TXT, and RTF. Colour/Greyscale: TIFF, JPEG, PDF, PDF/A, Compact PDF, Encrypted PDF, XPS, Searchable PDF, DOCX, XLSX, PPTX, TXT and RTF. Internet Fax: TIFF-FX, TIFF-F, TIFF-S[1]
Scan Destinations	Email, Desktop, FTP, Folder (SMB), USB, Internet fax (option), Super G3 fax (option)

Network Scanning System (continued)

One-touch Destinations	Up-to 2,000 (combined scan destinations)
Group Destinations	Up-to 500
Programs	48 (combined)
Max. Jobs	Up-to 100
Enhanced Email Integration	Standard Gmail connector, standard Exchange connector
Scanning Protocols	HTTP/HTTPS, FTP/FTPS, SMTP/SMTP-SSL/ESMTP, SMB, POP3, LDAP, S/MIME
Software	Sharpdesk® desktop personal document management software (1 user license included), Sharpdesk Mobile (download)

3K Stacking 65-Sheet Staple Finisher (MXFN34 option)

Type	3,000-sheet console staple finisher (65-sheet stapling)
Output Trays	Top tray: 250 sheets (letter size, non-stapled) Lower tray: Moving offset tray (up-to 3,000 letter size sheets)
Stapling Capacity	Up-to 65 sheets (letter)
Stapling Media	Plain paper, letter/legal/ledger size or mixed
Stapling Positions	1 front, 1 rear, or 2 point stitching

3K Stacking 65-Sheet Staple/Saddle-Stitch Finisher (MXFN35 option)

Type	3,000-sheet console staple finisher (65-sheet stapling)
Output Trays	Top tray: 250 sheets (letter size, non-stapled) Lower tray: Moving offset tray (up-to 3,000 letter size sheets)
Stapling Capacity	Up-to 65 sheets (letter)
Stapling Media	Plain paper, letter/legal/ledger size or mixed
Stapling Positions	1 front, 1 rear, or 2 point stitching
Saddle-Stitch	2-point centre stitch and bi-folding letter/legal/ledger
Saddle-Stitch Max. Sets	Up-to 10 sets (11-20 sheets per set)/15 sets (6-10 sheets per set)/25 sets (1-5 sheets per set)

Optional Equipment

MXLC18	Large Capacity Tray (letter)
MXLC19	Large Capacity Tray (ledger)
MXLT10	Long Paper Feeding Tray
MXFN33	Inner Finisher[1]
MXFN34	3K Stacking 65-sheet Staple Finisher[1]
MXFN35	3K Stacking 65-sheet Staple/Saddle-Stitch Finisher[1]
MXFN21	4K Stacking 100-sheet Staple Finisher[1]
MXFN22	4K Stacking 100-sheet Staple/Saddle-Stitch Finisher[1]
MXPN16B	3-Hole Punch Unit (requires MXFN34/35)
MXPN13B	3-Hole Punch Unit (requires MXFN21/22)
MXSC11	Staple Cartridge for MXFN34, MXFN35
MXSC12	Staple Cartridge for MXFN35
MXSCX1	Staple Cartridge for MXFN33, MXFN22
MXSCX2	Staple Cartridge for MXFN21, MXFN22
MXRB13	Relay Unit[1]
MXRB24	Paper Pass Unit for MXFN33
MXRB26	Paper Pass Unit[1]
MXRB27	Curl Correction Unit[1]
MXTM10	Trimmer Unit (requires MXFN22)
MXCF11	2-Tray Inserter Unit[1]
MXFD10	Multi-folding Unit[1]
MXTR21	Right Side Exit Tray
MXTU15	Centre Exit Tray
MXPF10	Bar Code Font Kit
MXFX15	Fax Expansion Kit
ARSU1	Stamp Unit (requires ARSV1 Stamp Cartridge)
ARSV1	Stamp Cartridge (required for ARSU1 Stamp Unit)
MXFWX1	Internet Fax Expansion Kit
MXFR60U	Commercial Data Security Kit (available shortly after launch)
MXAMX1L	Application Integration Module
DVENDFSV	Generic Vendor Interface Kit

Supplies

MX754NT	Toner Cartridge
MX754NV	Developer
MX754DR	Drum
MX700HB	Toner Collection Container

[1] Some features require optional equipment. See your local dealer.

[2] May vary depending on product configuration, machine settings and operating and/or environmental conditions.

[3] Go to www.sharp.ca for a list of supported devices and operating systems.

SHARP

Be Original.